

Remove old felt and clean any residual adhesive from bottom of skate holder. Peel off back from new felt and install. **IMPORTANT:** You will now need to recalibrate your skate holder. Follow instructions for calibration in owner's manual or training video. Instructions are also available on our website.

www.wissota.com

(952) 417-6611

Remove old felt and clean any residual adhesive from bottom of skate holder. Peel off back from felt and install. **IMPORTANT:** You will now need to recalibrate your skate holder. Follow instructions in owner's manual or training video. If misplaced, manuals and videos are available from factory.

www.wissota.com

(952) 417-6611

Remove old felt and clean any residual adhesive from bottom of skate holder. Peel off back from felt and install. **IMPORTANT:** You will now need to recalibrate your skate holder. Follow instructions in owner's manual or training video. If misplaced, manuals and videos are available from factory.

www.wissota.com

(952) 417-6611

Remove old felt and clean any residual adhesive from bottom of skate holder. Peel off back from felt and install. **IMPORTANT:** You will now need to recalibrate your skate holder. Follow instructions in owner's manual or training video. If misplaced, manuals and videos are available from factory.

www.wissota.com

(952) 417-6611

Remove old felt and clean any residual adhesive from bottom of skate holder. Peel off back from felt and install. **IMPORTANT:** You will now need to recalibrate your skate holder. Follow instructions in owner's manual or training video. If misplaced, manuals and videos are available from factory.

www.wissota.com

(952) 417-6611

Remove old felt and clean any residual adhesive from bottom of skate holder. Peel off back from felt and install. **IMPORTANT:** You will now need to recalibrate your skate holder. Follow instructions in owner's manual or training video. If misplaced, manuals and videos are available from factory.

www.wissota.com

(952) 417-6611

Remove old felt and clean any residual adhesive from bottom of skate holder. Peel off back from felt and install. **IMPORTANT:** You will now need to recalibrate your skate holder. Follow instructions in owner's manual or training video. If misplaced, manuals and videos are available from factory.

www.wissota.com

(952) 417-6611